

Product Description:

Introducing the stylish CurveE™ LED downlight range, this low glare downlight has a sleek baffled design with the light source recessed back to reduce glare. Available in matt white these triac dimmable downlights are an ideal non-fire rated solution for hospitality and residential applications in areas where fire rating is not required.

Product Image:




CurveE™ 7W Baffled Dimmable IP44 LED Downlight


Product Features:

- Baffled design for low glare - LED recessed by 10mm or 20mm
- Plug and play remote driver for easy installation
- IP44 rated - ideal for hospitality and residential applications such as corridors, living areas, bedrooms, dining rooms and zone 2 of bathrooms
- UGR19 (Unified Glare Rating)
- 1.5kV surge protection
- 3 year warranty

Line Drawing Image



Polar Curve Image



Product Specs:

| | | | |
|-------------------------------|-------|-------------------------------|-------------|
| Technology | LED | Luminaire Distribution | Direct |
| Lifetime L70 (hrs) | 25000 | Input Voltage | 220~240V AC |
| Dimmable | Yes | Dali | No |
| IP Rating | IP44 | Operating Env. Temp. (Min) °C | -20 |
| Operating Env. Temp. (Max) °C | 45 | Power Factor | 0.90 |
| Overall Diameter (mm) | 80 | Recess Depth (mm) | 75 |
| Cutout Diameter (mm) | 70 | Lamp Base | None |
| Height (mm) | 50 | Surge Protection (kV) | 1.5 |
| SDCM | 6 | | |

SKU Table and Ordering

| SKU Code | Wattage | Lumens | Lumens/Watt | Colour | Beam Angle | Ra | SDCM |
|-----------------|---------|--------|-------------|--------|------------|----|------|
| EN-DLB071D/30 | 7 | 640 | 91.43 | 3000 | 60 | 80 | 6 |
| EN-DLB071D/40 | 7 | 680 | 97.14 | 4000 | 60 | 80 | 6 |
| EN-DLB071DDA/30 | 7 | 640 | 91.43 | 3000 | 60 | 80 | 6 |
| EN-DLB071DDA/40 | 7 | 680 | 97.14 | 4000 | 60 | 80 | 6 |
| EN-DLB071DV/30 | 7 | 640 | 91.43 | 3000 | 60 | 80 | 6 |
| EN-DLB071DV/40 | 7 | 680 | 97.14 | 4000 | 60 | 80 | 6 |

Compliance & Approvals:



Warranty

This product has a warranty period of 3 Years. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.

UK Enlite Sales & Distribution
Apex Park
6 Little Burrow
Welwyn Garden City AL7 4SW
United Kingdom
Tel : +44 (0) 1707 35 18 20