

Bluetooth



mPRO™BX

Description:

- Tuneable white colour temperature between 2700-5000K
- 0-100% Dimming range
- Delivers up to 83lm/W
- 60° beam angle for maximum light distribution
- Acoustic and air leakage rated
- Can be covered by any insulation
- Convertible driver concept – reduced recess depth to 56mm for shallow ceiling voids
- BLE 4.0 MESH protocol means no gateway or router is required

Technical Specification:

Model:	AU-A1BTMPRO1BX
Input Voltage:	220~240V AC
Power Factor:	0.85
Lifetime L70 (hrs):	40000
Acoustic Rated:	Yes
Air Leakage Rated:	Yes
Dimmable:	Yes

Overall Diameter (mm):	88
Height (mm):	110
Cutout (mm):	68
IP Rating:	IP65
Luminaire Distribution:	Direct
Operating Temp:	-20°C to +40°C
Wireless Protocol:	Bluetooth 4.0

SKU Table and Ordering:

SKU Code:	Wattage:	Colour:	Lumen Range:	Lumens/Watt:	Beam Angle:
AU-A1BTMPRO1BX	7W	2700-6500K	520lm - 580lm	83 lm/W	60°

Warranty:

This product has a guarantee period of 3 years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice. Register at auroralighting.com/warranty

Certifications:

- Conforming to CE, RoHS and REACH directives
- Bluetooth 4.0