







REGOLA TRACKLIGHT

Colours

Housing Aluminium, die cast, plastic driverbox

 \bigcirc \bullet

Module Osram PrevaLED Core

Driver incorporated in track adapter

Light output module 3000lm*

CCT 2700K, 3000K, 4000K*

CRI >80Ra, >90Ra


Beam angles 40°

Adapter Powergear® 3-phase Ultimate adapter included

Rotatable 350° Tiltable 90° LED modules Standard CASAMBI, DALI Dimming options Filter options Not available Weight 1100 grams 50.000h (L80/B20) Expected lifetime Photobiological safety RG1 unlimited

Power factor > 0.9 Colour consistency 3 SDCM

Warranty 5 years warranty on LED module and driver









Available LED modules:

Description	Lumen ¹	Watt²	lm/W	сст	CRI
Osram PrevaLED G7	2000lm	15W	133	827, 830, 840	>80
Osram PrevaLED G7	2000lm	17W	117	927, 930, 940	>90
Osram PrevaLED G7	3000lm	18W	166	827, 830, 840	>80
Osram PrevaLED G7	3000lm	22W	136	927, 930, 940	>90

LED modules

Standard: CRI>80 and >90 in CCT 2700K, 3000K, 4000K

Premium White (PW): for fresh white and depth of colour in retail environments

Premium Ambiance (PA): cosy warm light (2200K) for hospitality projects

Premium Color (PC): perfect whites, crisp black

Dim-to-Warm (DtW): varies the CCT by dimming
Food Warm White (FWW): enhances the appearance of fresh bread, fruit and vegetables

Meat (MPR) and Fresh Fish (FF): enhances the appearance of meat or fish with low loss of products by discolouration

1) Lumen output of LED module (COB)

²) Mentioned wattage applies for the COB only. Wattage can differ (max.+/-5%) when multiple CCT is mentioned. The power of the complete fixture will be slightly higher due to the power consumption of the driver.











